



# Environmental Product Declaration

as per ISO 14025 and EN 15804

Owner of the declaration: BauMineral GmbH

Publisher: BCS Öko-Garantie GmbH - Ecobility Experts

Programme holder: BCS Öko-Garantie GmbH - Ecobility Experts

Declaration number: EPD-Baumineral-031-DE

Issue date: 11.12.2017

Valid to: 11.12.2022



## Grobalith® D4

This Environmental Product Declaration (EPD) refers to 1 t bottom ash from the power plant Datteln, Block 4. Bottom ash is a coal combustion byproduct. It is used as a construction material in structural and civil engineering.

**BauMineral**  
KraftWerkstoffe



## 1. General information

### BauMineral GmbH

#### Programme holder

BCS Öko-Garantie GmbH - Ecobility Experts  
Mariendorfbogen 3-5  
90402 Nürnberg  
Deutschland/Germany

#### Declaration number

EPD-Baumineral-031-DE

#### This declaration is based on the Product Category Rules

“Produktkategorieregeln für Kraftwerksnebenprodukte – Anforderungen an Umwelt-Produktdeklarationen für Kraftwerksnebenprodukte”

Product category rules for power plant by-products – requirements on Environmental Product Declaration for power plant by-products

issue 2017-06

(tested and approved by the independent expert committee)

#### Issue date

11.12.2017

#### Valid to

11.12.2022

#### Signature

Ppa. Frank Huppertz  
(President of Kiwa BCS Öko-Garantie GmbH - Ecobility Experts GmbH)

#### Signature

Prof. Dr. Frank Heimbecher  
(Chairman of the independent expert committee BCS Öko-Garantie GmbH – Ecobility Experts GmbH)

### Grobalith® D4

#### Owner of the declaration

BauMineral GmbH  
Hiberniasstraße 12  
D-45699 Herten

#### Declared product/ declared unit

1 t bottom ash

#### Scope

Grobalith® D4 is a bottom ash from the power plant Datteln, Block 4. Bottom ash is produced during electricity generation in hard coal-fired power stations.

Bottom ashes fall to the bottom of the combustion chamber and are collected in a water-filled hopper at the boiler end. The declaration is valid for bottom ash Grobalith® D4 by BauMineral GmbH.

The owner of the declaration shall be liable for the underlying information and evidence.

BCS Öko-Garantie GmbH – Ecobility Experts shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.

#### Verification

The CEN Norm EN 15804 serves as the core PCR

Independent verification of the declaration and data according to ISO 14025

internally

externally

#### Signature

Dr. Stephanie Schuler,  
(Intern verifier of Kiwa GmbH)



## 2. Product

### 2.1 Product description

Bottom ash Grobalith® D4 is produced in the boiler room of the power plant D4, resulting from the agglomerated, melted mineral compounds of hard coal and thus a coal combustion byproduct. Bottom ash is not extracted with the flue gases, but collected in a water-filled hopper at the boiler end. Due to its physical properties bottom ash is applicable in a large variety. Similar to hard coal fly ash its chemical-mineralogical composition results from the used type of coal and varies from residual carbon and minerals to trace elements. Bottom ash is highly porous and in terms of its particle density comparable with natural lightweight aggregates. Bottom ash has irregularly ruptured, coarse surfaces and is suitable for the production such as light concrete products and light bricks.

### 2.2 Application

According to DIN EN 13055 bottom ash Grobalith® is used in the construction industry as lightweight aggregate for concrete, mortar and grout. It is suitable for the production of light concrete products and light bricks, D4ich are typified by low weight and good heat insulating features. Other fields of application for bottom ash Grobalith® include road construction, as well as backfilling, embanking and soil improvement measures.

### 2.3 Technical Data

The technical data for the bottom ash Grobalith® D4 is shown in the following table. The values refer to the yearly average value of 2015.

Name	Value	Unit
Elutriable components grain content < 0,063 µm	< 10	M.-%
Elutriable components after impact stress at Proctor test	< 15	M.-%
Grain solidness – value of slag disintegration	25 – 35	M.-%
Bulk density /EN 1744-1; DIN EN 10355-1/	0,6 – 0,8	t/m <sup>3</sup>
Particle density /EN 1097-6:2000, appendix C/	1,1 -1,4	t/m <sup>3</sup>
Water absorption /EN 1097-6:2000 appendix C/	20 - 30	M.-%
Moisture content	25 -35	M.-%
Loss on ignition/EN 1744-1; DIN EN 10355-1/	< 10	M.-%
Sulphur /EN 1744-1/	< 1	M.-%
Sulphate acid-soluble /EN 1744-1/	0,1	M.-%
Chloride /EN 1744-1/	< 0,01	M.-%

### 2.4 Placing on the market / Application rules

Quality management of bottom ash conforms to DIN EN 13055-1. The accomplishment of the requirements of DIN EN 13055-1 is marked with a CE-Label. For the placing on the market (EU) No.305/2011 dated from 9 March applies. For the application and use of the products the European provisions apply.

### 2.5 Base materials / Ancillary materials

The composition of hard coal fly ash depends on the mineral components of the applied combustible, which is mainly composed of hard coal. In the following table average values of main components of EFA Füller® hard coal fly ash are given.



Parameter	Value	Unit
SiO <sub>2</sub>	55	M.-%
Al <sub>2</sub> O <sub>3</sub>	23	M.-%
Fe <sub>2</sub> O <sub>3</sub>	7	M.-%
CaO	4	M.-%
MgO	2	M.-%
K <sub>2</sub> O	2	M.-%
Na <sub>2</sub> O	1	M.-%

## 2.6 Manufacture

Bottom ash Grobalith® occurs inevitably as a solid, disperse residue during the combustion process in the power station. The aim of the power plant is the generation of electricity and heat. Bottom ash is produced in dry firing boilers and collected in a water-filled hopper at the end of the boiler, which seal the boiler hermetically. Bottom ashes are stored in heaps on the power plant site and transported with trucks to the customer. Generally, the trucks transport 25 to 27 t of bottom ash.

## 2.7 Reference service life

The declaration of Reference service life is voluntarily, since the extent of the study is not considering the whole life cycle of the bottom ash. Bottom ash is used as lightweight aggregate in concrete products. According to the BBSR-table 2011 / Nr. 363.512 the reference service life of concrete components amounts to ≥ 50 years.

## 3. LCA: Calculation rules

### 3.1 Declared unit

The declared unit is 1 t of bottom.

	Value	Unit
Declared unit	1	t
Conversion factor to 1 kg	1000	-

### 3.2 System boundary

The Environmental Product Declaration is a cradle-to-gate EPD, i.e. all potential environmental impact are considered from cradle until factory gate. The generation of bottom ash during the power production with hard coal is inevitable. The aim of a hard coal power station is the production of energy; therefore the potential environmental impacts of the energy production are allocated to the power station. For this reason, the combustion chamber is located is beyond the system boundary. All transport and storage processes (until the factory gate) are inside the system boundary. Thus, the system boundary of the manufacturing stage is the finished product at the factory gate. According to DIN EN 15804 this corresponds to the product phases A1-A3.

### 3.3 Estimates and assumptions

The power station Heyden in Petershagen is assumed as the reference power station, because all consumptions due to transports and energy are equal for the different power station, which are the source for bottom ashes from Baumineral. The data regarding Grobalith® D4 represents the consumption of all fly ashes from Baumineral.



The bottom ash is stored in heads on the respective power plant site and transported with trucks to the customer. Generally, the trucks transport 25 to 27 t of bottom ash. During the storage stage in heads no additional expenses occur (no heating, no cooling, no aeration) and thus no energy consumption. The estimated distance between bottom ash storage site and factory gate is 500m, which is the worst-case-scenario for all power stations. A truck of 27 t maximum payload and 40 t total weight is presumed (diesel vehicle). The occupancy rate is assumed as 85 percent.

### **3.4 Cut-off criteria**

All process specific data is compiled for the production modules A1 to A3. All flows that contribute more than 1 % to the total mass, energy or environmental impact of the system, are considered in the LCA. It can be assumed that the sum of all neglected processes is less than 5 % of all considered impact categories.

### **3.5 Period under review**

The data set employed in the EPD is based on 2015 production data.

### **3.6 Comparability**

Basically, a comparison or an evaluation of EPD data is only possible if all the data sets were created according to the EN 15804. Product-specific characteristics must be considered. Secondary data for the stage of manufacture is exclusively obtained from the database Gabi 6.

## **4. LCA: Scenarios and additional technical information**

No scenarios were analysed in this EPD.



## 5. LCA: Results

The following tables show the results of the indicators of the impact assessment, the resource input as well as the waste materials and other output-flows. The here shown results refer to the declared unit.

Description of the system boundary (X = Included in LCA; MND = Module not declared)																
Product stage			Construction process stage		User stage						End of life stage			Benefits and loads beyond the system boundaries		
Raw material supply	Transport	Manufacturing	Transport from manufacturer to place of use	Construction-installation process	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction / demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
X	X	X	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND

### Results of the LCA – Environmental impact: 1 t bottom ash Grobalith®D4

Parameter	Unit	A1 – A3
Global warming potential	[kg CO <sub>2</sub> -Eq.]	2,35E-02
Depletion potential of the stratospheric ozone layer	[kg CFC11-Eq.]	2,90E-14
Acidification potential of land and water	[kg SO <sub>2</sub> -Eq.]	1,04E-04
Eutrophication potential	[kg (PO <sub>4</sub> ) <sup>3-</sup> -Eq.]	2,84E-05
Formation potential of tropospheric ozone photchemical oxidants	[kg Ethen-Eq.]	-3,59E-05
Abiotic depletion potential for non fossil resources	[kg Sb-Eq.]	1,21E-09
Abiotic depletion potential for fossil resources	[MJ]	3,20E-01

### Results of the LCA – Resource use: 1 t bottom ash Grobalith®D4

Parameter	Unit	A1 – A3
Renewable primary energy as energy carrier	[MJ]	2,45E-02
Renewable primary energy resources as material utilization	[MJ]	IND
Total use of renewable primary energy resources	[MJ]	2,45E-02
Non renewable primary energy as energy carrier	[MJ]	3,21E-01
Non renewable primary energy as material utilization	[MJ]	IND
Total use of non renewable primary energy resources	[MJ]	3,21E-01
Use of secondary material	[kg]	IND
Use of renewable secondary fuels	[MJ]	IND
Use of non renewable secondary fuels	[MJ]	IND
Use of net fresh water	[m <sup>3</sup> ]	1,41E-05

### Results of the LCA – Output flows and waste categories: 1 t bottom ash Grobalith®D4

Parameter	Unit	A1 – A3
Hazardous waste disposed	[kg]	2,59E-07
Non hazardous waste disposed	[kg]	2,16E-03
Radioactive waste disposed	[kg]	4,27E-07
Components for re-use	[kg]	IND
Materials for recycling	[kg]	IND
Materials for energy recovery	[kg]	IND
Exported electrical energy	[MJ]	IND
Exported thermal energy	[MJ]	IND



## 6. LCA: Interpretation

The potential environmental impacts of bottom ash result from the storage and transport. No indirect environmental aspects occur during the storage in heaps. The environmental effects of bottom ash production are caused by the transport.

The photochemical Formation potential of tropospheric ozone (POCP) has an overall negative value. It is caused by the direct emission during transport. The ozone is decomposed by the reaction with the emitted nitrogen monoxide, thus nitrogen dioxide and oxygen are formed. This has a positive effect on the photochemical formation potential of tropospheric ozone (POCP).

## 7. References

- [1] GaBi 6: Software und Datenbank zur Ganzheitlichen Bilanzierung. LBP, Universität Stuttgart und PE INTERNATIONAL, 2015
- [2] CML-IA April 2013 – Charakterisierungsfaktoren entwickelt durch Institut of Environmental Sciences (CML): Universität Leiden, Niederlande - <http://www.cml.leiden.edu/software/data-cmlia.html>
- [3] Kreissig & Kümmel 1999 – Baustoff-Ökobilanzen. Wirkungsabschätzung und Auswertung in der Steine-Erden-Industrie. Hrsg. Bundesverband Baustoffe Steine + Erden e.V.
- [4] BBSR, BNB 2011, Nutzungsdauern\_von\_Bauteilen Tabelle 2011 / Nr. 363.513, 2011-11-03.
- [5] InformationsZentrum Beton GmbH – Erläuterungen zu den Umweltproduktdeklarationen für Beton. 2014.
- [6] Bundesvereinigung Recyclingbaustoffe e.V. – Monitoringbericht zum Aufkommen und Verbleib mineralischer Bauabfälle. 2010.
- Kiwa BCS Öko-Garantie GmbH – Ecobility Experts (Hrsg):
  - [7] Produktkategorieregeln für Kraftwerksnebenprodukte: Anforderungen Umweltproduktdeklarationen für Kraftwerksnebenprodukte; 2017-06
  - [8] Allgemeine Produktkategorieregeln für Bauprodukte: Rechenregeln für die Ökobilanz und Anforderungen an den Hintergrundbericht; 2017-06
  - [9] Allgemeine Programmanleitung aus dem EPD-Programm der Kiwa BCS öko-Garantie GmbH – Ecobility Experts; 2017-06 Normen und Gesetze
  - [10] DIN EN ISO 14040: 2009-11: DIN Deutsches Institut für Normung e.V.: Umweltmanagement – Ökobilanz – Grundsätze und Rahmenbedingungen, Beuth Verlag. Berlin, 2009.
  - [11] DIN EN ISO 14044: 2006-10: DIN Deutsches Institut für Normung e.V.: Umweltmanagement – Ökobilanz – Anforderungen und Anleitungen, Beuth Verlag. Berlin, 2006.
  - [12] DIN EN ISO 14025:2011-10: DIN Deutsches Institut für Normung e.V.: Umweltkennzeichnungen und –deklarationen – Typ III Umweltdeklarationen - Grundsätze und Verfahren, Beuth Verlag. Berlin, 2011.
  - [13] DIN EN 4501: DIN Deutsches Institut für Normung e.V.: Flugasche für Beton, Teil 1: Definition, Anforderungen und Konformitätskriterien, Beuth Verlag. Berlin, 2012. Tei2: Konformitätsbewertung, Beuth Verlag. Berlin, 2005.



**BauMineral**

KraftWerkstoffe

[14] DIN EN 1045-2: DIN Deutsches Institut für Normung e.V.: Tragwerke aus Beton, Stahlbeton und Spannbeton, Teil 2: Beton – Festlegung, Eigenschaften, Herstellung und Konformität – Anwendungsregeln zu DIN EN 206-1, Beuth Verlag. Berlin, 2008.

[15] DIN EN 206-1: DIN Deutsches Institut für Normung e.V.: Beton, Teil 1: Festlegung, Eigenschaften, Herstellung und Konformität, Beuth Verlag. Berlin, 2005.

[16] DIN ISO 13055-1: DIN Deutsches Institut für Normung e.V.: Leichte Gesteinskörnung – Teil 1: Leichte Gesteinskörnungen für Beton, Mörtel und Einpressmörtel, Beuth Verlag Berlin, 2002

	<b>Publisher</b> Kiwa BCS Öko-Garantie GmbH – Ecobility Experts Marientorbogen 3-5 90402 Nürnberg Deutschland/Germany	Mail Web	<a href="mailto:ecobility@bcs-oeko.de">ecobility@bcs-oeko.de</a> <a href="http://www.kiwabcs.com/ecobility">www.kiwabcs.com/ecobility</a>
	<b>Programme holder</b> Kiwa BCS Öko-Garantie GmbH – Ecobility Experts Marientorbogen 3-5 90402 Nürnberg Deutschland/Germany	Mail Web	<a href="mailto:ecobility@bcs-oeko.de">ecobility@bcs-oeko.de</a> <a href="http://www.kiwabcs.com/ecobility">www.kiwabcs.com/ecobility</a>
	<b>Author of the Life Cycle Assessment</b> Kiwa GmbH Voltastr. 5 13355 Berlin Germany	Tel. Fax. Mail Web	030/467761-43 030/467761-10 <a href="mailto:Juliane.Pluempe@kiwa.de">Juliane.Pluempe@kiwa.de</a> <a href="http://www.kiwa.de">www.kiwa.de</a>
<b>BauMineral</b> KraftWerkstoffe	<b>Owner of the declaration</b> BauMineral GmbH Hiberniasstraße 12 D-45699 Herten	Tel. Fax. Mail Web	02366/509-0 02366/509-256 <a href="mailto:baumineral@baumineral.de">baumineral@baumineral.de</a> <a href="http://www.baumineral.de">www.baumineral.de</a>